

Insulation Vacuum Loader

Remove old cellulose insulation from ceiling spaces with our Insulation vacuum loader through fan vacuum system.

Using a large diameter 5 inch vacuum hose this machine will rapidly remove cellulose insulation in a fraction of the time compared with manual bagging methods.

Cellulose and Rockwool fibre insulation removal is vacuumed via the machines solid steel constructed 6mm thick 400mm impeller . The material is vacuumed and directed into our optional supply exit trunking then into the vertical load collection bag, material can also be blown into a caged/ shade cloth lined trailer.

Most operators prefer the optional vertical load bag system as this allows the waste material to be disposed of at refuse sites.

Featuring a thick steel fan scroll with liners and replaceable impeller this Insulation vacuum machine will pay for it self very quickly. Powered by a Vangaurd V twin 18hp petrol engine with adjustable engine speed, this unit is an extremely reliable and rugged contractor grade machine.

As a rapid recovery machine it is perfect for fast and reliable blow in ceiling insulation removal. System comes

(Photo shows fully optioned model)

For more info call
+61 3 9769 1211



DIMENSIONS

72 L x 72 W x 112 H cm Weight - 129kg

Insulation Vacuuming made *easy*



STANDARD & OPTIONAL

3 year warranty on engine

Optional wheel system can be fitted

3500 cfm airflow

Optional 180 degree discharge and bag system

400mm OD, 6mm thick steel vacuum fan

Economically priced 400 litre waste bags

Wear plates fitted in the fan housing

30 metres of 5 inch clear vacuum hose

Rugged design and reliable performance

18HP Briggs & Stratton Vanguard engine

TYPICAL APPLICATIONS

Cellulose Fibre

Rockwool Fibre

